



SPECIFICATION DATA SHEET (effective 11/30/07)

IR41F Continuous Rolls/Sheets

Physical Properties

Polymer			CR/NBR/PVC
Color			Black
Classifications			
ASTM D 1056-68			SBE41
ASTM D 1056-00			2B1
Suffix Requirements			B2, C1, F1, M
1. 25% Compression Resistance (psi) 3/8" & higher	ASTM D 1056		2.0 – 5.0
25% Compression Resistance (psi) 1/4" & less	ASTM D 1056		5.5 – 8.5
2. 50% Compression Set (%)	ASTM D 1056		25 max.
3. Density (lb/ft ³) 3/8" & higher	ASTM D 1056		4.0 – 7.0
Density ((lb/ft ³) 1/4" & less	ASTM D 1056		7.5 – 10.5
4. Water Absorption (lb./ft ²)	ASTM D 1667		0.1 max.
5. Tensile (psi)	ASTM D 412		50 min.
6. Elongation (%)	ASTM D 412		100 min.
7. Flammability (1)			
FMVSS302	0 Burn Rate		Pass
UL 94	HF-1 @ 1/8"		Pass
8. Ozone Resistance (GM4486P)	No Cracking		Pass
9. FAR 25.853 (12 Second Vertical Burn Test) (4)	@ 1/8" Skin 2 Side		Pass
10. Temperature Use (2)	ASTM D-1056	Cold Crack	-40°F
		High (3)	200
Standard Roll Widths (in)			48" and 54"
Maximum Gauge (in)			1.00"

(1) Flammability – This item and any corresponding data refer to typical performance in the specific test indicated and should not be construed to imply this material's behavior in other fire conditions.

(2) This recommendation is based on polymer type only. For specific application requirements please contact technical service

(3) This temperature is the maximum allowable for intermittent exposure only. For continuous use temperature please contact technical service department.

(4) Lot certification must be requested on P.O. Lead times will be longer for lot certifications.

NBR – Acrylonitrile Butadiene Rubber

PVC - Polyvinyl Chloride

CR – Chloroprene (Neoprene®)

Available skin 2 sides 1/8" – 1.0"

Other gauges and widths may be available. Please contact Customer Service.

Note: SAEJ 18 is equivalent to ASTM D-1056

**Seal & Design
Able Division**

5533 Steeles Avenue West Unit 11
Toronto, Ontario M9L 1S7
Ph: (416) 741-0750
Gasket@AbleSealAndDesign.com

**Seal & Design
Corporate Headquarters**

4015 Casilio Parkway
Clarence, NY 14031
Ph: (716) 759-2222
Info@SealAndDesign.com
www.SealAndDesign.com

**Seal & Design
Higbee Division**

6741 Thompson Rd N
Syracuse, NY 13221
Ph: (315) 432-8021
Sales@Higbee-Inc.com