



## FLEXSEAL® LMF, LTG and STG Gaskets

### FOR MALE-FEMALE AND TONGUE AND GROOVE FLANGES


- › Spiral winding of preformed metal and soft filler material-for use where no space is provided for a compression guide ring
- › Inner diameter of windings is reinforced with several plies of metal without filler to give greater stability
- › Made with the CONTROLLED DENSITY® process which ensures that the optimum filler density is constant across the windings for consistent compression and superior sealability
- › Style LMF - windings only fit for large male-female flanges
- › Style LTG - windings only fit for large tongue and groove flanges
- › Style STG - windings only fit for small tongue and groove flanges

### ORDERING INFORMATION


When ordering, specify:

- › Nominal pipe size
- › Pressure rating
- › Winding materials (304 SS is standard, filler material must be specified)
- › Thickness of winding (0.125" is standard)

### Male-Female



### Tongue and Groove



### Seal & Design Able Division

5533 Steeles Avenue West Unit 11  
Toronto, Ontario M9L 1S7  
Ph: (416) 741-0750  
Gasket@AbleSealAndDesign.com

### Seal & Design Corporate Headquarters

4015 Casilio Parkway  
Clarence, NY 14031  
Ph: (716) 759-2222  
Info@SealAndDesign.com  
[www.SealAndDesign.com](http://www.SealAndDesign.com)

### Seal & Design Higbee Division

6741 Thompson Rd N  
Syracuse, NY 13221  
Ph: (315) 432-8021  
Sales@Higbee-Inc.com