



FLEXSEAL® RW

ADVANTAGES

- › Made with the CONTROLLED DENSITY® process which ensures that the optimum filler density is constant across the windings for consistent compression and superior sealability
- › Durable; easy installation and removal
- › Seals pressures to flange ratings, in accordance with ASME B16.5
- › Suited to temperatures from cryogenic to 2000°F (1093°C), depending on metal and filler.
- › Guide ring simplifies centering of sealing element on the flange face
- › Custom-tailored solutions accommodate a variety of conditions by combining various metals and filler materials

STYLE RW

- › General purpose gasket suitable for raised face flanges up to Class 2500
- › Centering ring accurately locates the gasket on the flange face, provides additional radial strength, and acts as a compression limiter
- › Spiral winding (sealing element) consists of preformed metal and soft filler material

Ordering Information

When ordering specify:

- › Nominal pipe size and pressure rating
- › Centering ring material
- › Winding and filler material



Seal & Design Able Division

5533 Steeles Avenue West Unit 11
Toronto, Ontario M9L 1S7
Ph: (416) 741-0750
Gasket@AbleSealAndDesign.com

Seal & Design Corporate Headquarters

4015 Casilio Parkway
Clarence, NY 14031
Ph: (716) 759-2222
Info@SealAndDesign.com
www.SealAndDesign.com

Seal & Design Higbee Division

6741 Thompson Rd N
Syracuse, NY 13221
Ph: (315) 432-8021
Sales@Higbee-Inc.com