

TR3 & TR5

Thermally Conductive Pressure Sensitive Transfer Adhesives

Saint-Gobain Performance Plastics **ThermaCool® TR3** and **TR5** are a unique series of thermally conductive pressure sensitive acrylic transfer adhesives. These adhesives are supplied with release liners on both sides for ease of converting. These materials allow an easy method to provide an adhesive layer to gap filler silicone materials and thermally conductive fabrics that are not supplied with integral adhesive. These materials can also be used in place of mechanical fasteners to bond heat sinks to components.

Physical Properties

Property	Test Method	TR3	TR5
Thickness (mils)	ASTM D1000	3.0	5.0
Thermal Conductivity (W/mK)	ASTM E1530	0.4	0.4
Thermal Impedance (°C in ² /W)	ASTM E1530 @ 10 psi	0.3	0.5
Dielectric Strength	ASTM D1000	N/A	N/A
Adhesion to Steel (oz./in.)	ASTM D1000	30	60
Adhesion to Liner (oz./in.)	ASTM D1000	Easy Release	Easy Release
Operating Temperature Range (°F)	—	-20 to 300	-20 to 300

All properties are typical values and should not be used for writing specifications.

Recommended Uses

Thermally conductive transfer adhesive can be applied to a wide range of materials to provide bonding between parts or to provide an adhesive layer to thermal fabrics or gap fillers that do not have a pressure sensitive adhesive applied.

Availability

Available as yard goods up to 40" wide.

ThermaCool® is a registered trademark
©2008 Saint-Gobain Performance Plastics Corporation
AFF-1276-PDF-0908-SGCS

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

Features/Benefits

- Thermally conductive transfer adhesive provides ability to customize parts in the field
- Compliant conductive adhesive minimizes effects of surface roughness and improves thermal performance
- Adhesive formulation is designed to exhibit excellent thermal properties at application pressures as low as 10 psi
- Specifically formulated adhesive allows parts to be reworked without damage to sensitive components
- High peel strength adhesion to minimize air entrapment

Applications

- Custom application of adhesives to gap fillers or thermally conductive fabrics
- Replacement of mechanical fasteners
- Pressure-sensitive adhesive tape can be pre-applied to a heat sink to minimize assembly costs
- Adheres to various surfaces to create a pressure sensitive laminate material



Seal & Design Corporate Headquarters

4015 Casilio Parkway
Clarence, NY 14031
Ph: (716) 759-2222
Info@SealAndDesign.com
www.SealAndDesign.com



Seal & Design Higbee Division

6741 Thompson Rd N
Syracuse, NY 13221
Ph: (315) 432-8021
Sales@Higbee-Inc.com



Seal & Design Able Division

5533 Steeles Avenue West Unit 11
Toronto, Ontario M9L 1S7
Ph: (416) 741-0750
Gasket@AbleSealAndDesign.com